

HIGH POWER ZOOM

B I N O C U L A R S

<GTR series>

GTR-94550 : 9-45×50 mm BCF

GTR-105060 : 10-50×60 mm BCF

GTR-126070 : 12-60×70 mm BCF



GTR-94550
GXR-126050

<GXR series>

GXR-126050 : 12-60×50 mm BCF

GXR-147060 : 14-70×60 mm BCF

GXR-168070 : 16-80×70 mm BCF



GTR-105060
GXR-147060

- Fully coated optics
- All glass lens use
- Rubber covering
- Tripod socket

OPTION

- Camouflage rubber covering
- BAK-4 porro prism
- L-shape tripod adapter
- I. R. Ruby coated objective lens



GTR-126070
GXR-168070



SPECIFICATIONS

ITEM NO.	MAGNIFICATION	OBJECTIVE LENS DIA.	FIELD OF VIEW	FIELD AT 1000 YDS	EXIT PUPIL	BRIGHTNESS	LENS ELEMENT		WEIGHT	SIZE (H)×(W)×(D)
							OCULAR	OBJECTIVE		
GTR-94550	9-45×	50 mm	3°-1.25°	157-65 FT.	5.5-1.1	30-1.2	6	2	980	185×176×75 mm
GTR-105060	10-50×	60 mm	2.7°-1.1°	141-57 FT.	6.0-1.2	36-1.4	6	2	1,170	206×185×80 mm
GTR-126070	12-60×	70 mm	2.25°-0.95°	118-50 FT.	5.8-1.2	34-1.4	6	2	1,470	246×195×80 mm
GXR-126050	12-60×	50 mm	1.9°-1°	100-53 FT.	4.2-0.8	17-0.7	6	3	980	185×176×75 mm
GXR-147060	14-70×	60 mm	1.6°-0.9°	84-47 FT.	4.3-0.8	18-0.7	6	3	1,200	206×185×78 mm
GXR-168070	16-80×	70 mm	1.4°-0.8°	73-42 FT.	4.4-0.9	19-0.8	6	3	1,470	246×195×80 mm

NEW STANDARD BINOCULARS



Good and fashionable design of rubber covered standard prismatic binoculars. The rubber exterior absorbs shocks and bumps, provide sure-grip under all other conditions.

SPECIFICATIONS


ITEM NO.	MAGNIFICATION	OBJECTIVE LENS DIA.	FIELD OF VIEW	FIELD AT 1000 YDS	EXIT PUPIL	BRIGHTNESS	LENS ELEMENT		WEIGHT	SIZE (H)×(W)×(D)
							OCULAR	OBJECTIVE		
RRC-830	8×	30 mm	8.2° W. A.	430 FT.	3.75 mm	14	3	2	510 g	113×167×50 mm
RRC-735	7×	35 mm	9.5° W. A.	500 FT.	5 mm	25	3	2	510 g	113×167×50 mm
RRC-840	8×	40 mm	8.2° W. A.	430 FT.	5 mm	25	3	2	600 g	137×174×51 mm
RRC-750	7×	50 mm	6.8°	356 FT.	7.1 mm	51	3	2	710 g	171×182×65 mm
RRC-1050	10×	50 mm	7° W. A.	367 FT.	5 mm	25	3	2	710 g	171×182×65 mm
RRC-1250	12×	50 mm	6° W. A.	314 FT.	4.16 mm	17	3	2	710 g	171×182×65 mm
RRC-1650	16×	50 mm	4.1° W. A.	215 FT.	3.12 mm	9.76	3	2	710 g	171×182×65 mm
RRC-2050	20×	50 mm	3.3° W. A.	173 FT.	2.5 mm	6.25	3	2	710 g	171×182×65 mm

*FIELD: W.A. = WIDE ANGLE

*All designs and specifications subject to change without notice.

<RR series>

- Rubber covering
- Fold-down rubber eyecup
- BK-7 porro prism
- Tripod socket



RR-830-GYR



RR-840-BR



RR-750-CR

<RRC series>

- Rubber covering
- Fold-down rubber eyecup
- BK-7 porro prism
- Internal center-focus
- Tripod socket



RRC-830-GYR



RRC-840-BR



RRC-1050-CR

OPTION

- Fully coated optics
- BAK-4 porro prism
- I. R. Ruby coated objective lens
- Camouflage rubber covering

COLOR

BR.....BLACK RUBBER
GYR.....GREY RUBBER
CR.....CAMOUFLAGE RUBBER

Syarikat E.J. Motiwalla

• 36 Persiaran Ampang • 55000 • Kuala Lumpur • MALAYSIA

• Tel: (603)42577786 • Fax: (603)42562922

• Emails: info@ejmotiwalla.com - sales@ejmotiwalla.com